

# P/N AN515B8R10

### **Description**

Fastener Length: 19/32", Thread: 8-32, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN515B8R10
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-151-2863
Schedule B:	7415.33.8050
FCCN:	FAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN515B8R10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Round
Head Diameter:	0.287 Inches Minimum And 0.309 Inches Maximum
Head Height:	0.120 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 1c Style

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN515B8R10">https://military-fasteners.com/screws/machine+screws/AN515B8R10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.