

Description

Fastener Length: 3/16", Thread: 4-40, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN515C43
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-227-0961
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN515C4-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Round
Head Diameter:	0.193 Inches Minimum And 0.211 Inches Maximum
Head Height:	0.086 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Material:	Steel Comp 301 Or Steel Comp 430
Screw Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	81348-ff-s-92 Government Specification And 88044-an515/canceled/ Government Standard
Nondefinitive Spec/std Data:	1 Type And 1s Style And 4-40 Size

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515C4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.