

**Description**

Fastener Length: 5/8", Thread: 4-40, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN515C4R10
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-487-6355
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N AN515C4R10 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.544 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.193 Inches Minimum And 0.211 Inches Maximum
<b>Head Height:</b>	0.086 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 430 Or Steel Comp 303 Or Steel Comp 303se
<b>Screw Material Document And Classification:</b>	Mil-s-7720 Mil Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Qq-s-764 Fed Spec 3rd Material Response Or Qq-s-764 Fed Spec 4th Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1c Style And 3 Type
<b>Departure From Cited Designator:</b>	As Mod By Material And Finish

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515C4R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.