



Military-Fasteners.com

P/N AN515DD8R6

Description

Fastener Length: 3/8", Thread: 8-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN515DD8R6
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-954-4606
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N AN515DD8R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515DD8R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.