

# **P/N AN515PB4R7**

### **Description**

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN515PB4R7

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-292-8602

Schedule B: 7415.33.8050

ECCN: 9A991

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN515PB4R7 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.388 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Round
Head Diameter:	0.193 Inches Minimum And 0.211 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

# **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN515PB4R7">https://military-fasteners.com/screws/machine+screws/AN515PB4R7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.