

Description

Fastener Length: 0-31/32", Thread: 6-32, Thread Length: 0-31/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | AN515UB6R16 |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5305-00-282-9477 |
| Schedule B: | 7415.33.8050 |
| ECCN: | 9A991 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N AN515UB6R16 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.969 Inches Minimum And 1.000 Inches Maximum |
| Fastener Length: | 0.969 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Height: | 0.103 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 1c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515UB6R16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.