

P/N AN515UB6R16

Description

Fastener Length: 0-31/32", Thread: 6-32, Thread Length: 0-31/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN515UB6R16

Minimum Qty (MOQ): 35 EA

NSN: 5305-00-282-9477

Schedule B: 7415.33.8050

ECCN: 9A991

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N AN515UB6R16 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.103 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN515UB6R16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN515UB6R16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/AN515UB6R16 and selecting the quantity you want https://military-fasteners.com/screws/AN515UB6R16 and selecting the property of the pr