

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 1-1/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN52010R18 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-144-3824 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |



P/N AN520-10R18 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.125 Inches Minimum |
| Fastener Length: | 1.125 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.334 Inches Minimum And 0.359 Inches Maximum |
| Head Height: | 0.137 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-671 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520-10R18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.