

Description

Fastener Length: 1-7/8", Thread: 10-32, Thread Length: 1-7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN52010R30
Minimum Qty (MOQ):	20
NSN:	5305-00-207-1208
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN520-10R30 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.812 Inches Minimum And 1.875 Inches Maximum
Fastener Length:	1.812 Inches Minimum And 1.875 Inches Maximum
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.137 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Departure From Cited Designator:	As Modified By Internal Drive Style And Location

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520-10R30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.