

P/N AN520-10R7

Military-Fasteners.com

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16", pan head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

Μ	S	3	5	2	0	7	-5	2	6	2	
	-	-	-	-	~			-	~	-	

SKU / Model:	AN52010R7
Minimum Qty (MOQ):	100
NSN:	5305-00-207-1205
Schedule B:	7318.15.6080
ECCN:	EAR99



P/N AN520-10R7 Specifications

Thread Direction:Right-handThread Length:0.438 Inches NominalFastener Length:0.438 Inches NominalHead Style:RoundHead Diameter:0.334 Inches Minimum And 0.359 Inches MaximumHead Height:0.137 Inches NominalInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Screw Material Document And Classification:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:Cadmium					
Thread Length:0.438 Inches NominalFastener Length:0.438 Inches NominalHead Style:RoundHead Diameter:0.334 Inches Minimum And 0.359 Inches MaximumHead Height:0.334 Inches NominalInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Kinimum Tensile Strength:Stoll Op unds Per Square InchScrew Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Thread Class:	2a			
Fastener Length:0.438 Inches NominalHead Style:RoundHead Diameter:0.334 Inches Minimum And 0.359 Inches MaximumHead Height:0.137 Inches NominalInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Strew Material:Sto00 Pounds Per Square InchScrew Material:Stel Comp 1010Screw Surface Treatment:Qq-s-633-canceled Fed Spec Single Material ResponseThread Series Designator:Unf	Thread Direction:	Right-hand			
Head Style:RoundHead Diameter:0.334 Inches Minimum And 0.359 Inches MaximumHead Height:0.137 Inches NominalInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:S5000 Pounds Per Square InchScrew Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Thread Length:	0.438 Inches Nominal			
Head Diameter:0.334 Inches Minimum And 0.359 Inches MaximumHead Height:0.137 Inches NominalInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:S5000 Pounds Per Square InchScrew Material:Stel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Fastener Length:	0.438 Inches Nominal			
Head Height:0.137 Inches NominalInternal Drive Style:0.137 Inches NominalNominal Thread Diameter:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:Sol00 Pounds Per Square InchScrew MaterialSteel Comp 1010Screw Material Document And Classification:Qq-s633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Head Style:	Round			
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:55000 Pounds Per Square InchScrew Material:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum			
Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:55000 Pounds Per Square InchScrew Material:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Head Height:	0.137 Inches Nominal			
Thread Quantity Per Inch:32Minimum Tensile Strength:55000 Pounds Per Square InchScrew Material:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Internal Drive Style:	Cross Recess Type 1			
Minimum Tensile Strength:55000 Pounds Per Square InchScrew Material:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Nominal Thread Diameter:	0.190 Inches			
Screw Material:Steel Comp 1010Screw Material Document And Classification:Qq-s-633-canceled Fed Spec Single Material ResponseScrew Surface Treatment:CadmiumThread Series Designator:Unf	Thread Quantity Per Inch:	32			
Screw Material Document And Classification: Qq-s-633-canceled Fed Spec Single Material Response Screw Surface Treatment: Cadmium Thread Series Designator: Unf	Minimum Tensile Strength:	55000 Pounds Per Square Inch			
Screw Surface Treatment: Cadmium Thread Series Designator: Unf	Screw Material:	Steel Comp 1010			
Thread Series Designator: Unf	Screw Material Document And Classification:	Qq-s-633-canceled Fed Spec Single Material Response			
	Screw Surface Treatment:	Cadmium			
Nondefinitive Spec/std Data: 3 Type And 1 Design And 1c Style	Thread Series Designator:	Unf			
	Nondefinitive Spec/std Data:	3 Type And 1 Design And 1c Style			

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/AN520-10R7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.