

P/N AN520-6R4

Description

Fastener Length: 7/32", Thread: 6-40, Thread Length: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN5206R4

Minimum Qty (MOQ): 95 EA

NSN: 5305-00-151-1242

Schedule B: 7318.15.4000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN520-6R4 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.200 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Height: | 0.103 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Or Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Departure From Cited Designator: | As Modified By Internal Drive Styl And Internal Drive Location |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN520-6R4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.