

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN520B10R12
Minimum Qty (MOQ):	145 EA
NSN:	5305-00-156-2899
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN520B10R12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.137 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520B10R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.