

**Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN520B10R12
Minimum Qty (MOQ):	145 EA
NSN:	5305-00-156-2899
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N AN520B10R12 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.334 Inches Minimum And 0.359 Inches Maximum
<b>Head Height:</b>	0.137 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 1c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520B10R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.