

# **P/N AN520B10R14**

### **Description**

Fastener Length: 7/8", Thread: 10-32, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN520B10R14
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-156-2900
Schedule B:	7415.33.8050
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN520B10R14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.137 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 1c Style

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN520B10R14">https://military-fasteners.com/screws/machine+screws/AN520B10R14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.