

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN520C10R12
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-282-4043
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN520C10R12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.137 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520C10R12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.