

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | AN520DD108 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-151-3795 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013680, Alum Screws |



* See page 2 for technical characteristics

P/N AN520DD10-8 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.334 Inches Minimum And 0.359 Inches Maximum |
| Head Height: | 0.137 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-267 Fed Spec Single Material Response Or Qq-a-268 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 1s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520DD10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.