

**Description**

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN520DD108
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-151-3795
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N AN520DD10-8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.334 Inches Minimum And 0.359 Inches Maximum
<b>Head Height:</b>	0.137 Inches Nominal
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Screw Material:</b>	Aluminum Alloy 2024
<b>Screw Material Document And Classification:</b>	Qq-a-267 Fed Spec Single Material Response Or Qq-a-268 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	1 Type And 1s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520DD10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.