

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN520DD108
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-151-3795
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N AN520DD10-8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Round
Head Diameter:	0.334 Inches Minimum And 0.359 Inches Maximum
Head Height:	0.137 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-267 Fed Spec Single Material Response Or Qq-a-268 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN520DD10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.