

## P/N AN525-10-14

### **Description**

Fastener Length: 29/32", Thread: 10-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN5251014
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-167-3893
Schedule B:	7318.15.6080
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN525-10-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.844 Inches Minimum And 0.906 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.025 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	100000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	An-p-61 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN525-10-14">https://military-fasteners.com/screws/machine+screws/AN525-10-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN525-10-14">https://military-fasteners.com/screws/machine+screws/AN525-10-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN525-10-14">https://military-fasteners.com/screws/machine+screws/AN525-10-14</a> and selecting the quantity you want then click "add to cart".