

Description

Fastener Length: 1-5/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN5251026 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-167-3899 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN525-10-26 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 1.625 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.375 Inches Nominal |
| Head Height: | 0.089 Inches Minimum And 0.099 Inches Maximum |
| Extended Washer Diameter: | 0.437 Inches Nominal |
| Extended Washer Thickness: | 0.025 Inches Minimum And 0.030 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 100000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-689 C4 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Zinc |
| Screw Surface Treatment Document And Classification: | An-p-61 Fed Spec 1st Treatment Response And Mil-p-6889 Ty 1 Mil Spec 2nd Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-10-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.