



Military-Fasteners.com

P/N AN525-10-26

Description

Fastener Length: 1-5/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5251026
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-167-3899
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN525-10-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	1.625 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.025 Inches Minimum And 0.030 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	100000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-689 C4 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Zinc
Screw Surface Treatment Document And Classification:	An-p-61 Fed Spec 1st Treatment Response And Mil-p-6889 Ty 1 Mil Spec 2nd Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-10-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.