

P/N AN525-10-7

Description

Fastener Length: 15/32", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN525107
Minimum Qty (MOQ):	50
NSN:	5305-01-316-8166
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN525-10-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum
Fastener Length:	0.407 Inches Minimum And 0.469 Inches Maximum
Head Style:	Fillister Extended Washer
Head Diameter:	0.375 Inches Minimum
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.025 Inches Minimum And 0.030 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN525-10-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN525-10-7 and selecting the quantity you