

Description

length: 11/16", grip: 9/32", thread: 10-32, cadmium plated steel, philips recess, AN525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN52510R11
Minimum Qty (MOQ):	50
NSN:	5305-00-180-0013
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN525-10R11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.396 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	0.656 Inches Minimum And 0.719 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.427 Inches Minimum And 0.447 Inches Maximum
Extended Washer Thickness:	0.025 Inches Minimum And 0.030 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium Or Zinc
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec 1st Treatment Response Or Qq-z-325,ty 2,cl 3 Fed Spec 2nd Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-10R11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.