

Description

length: 2", grip: 1-19/32", thread: 10-32, cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN52510R32 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-825-1209 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN525-10R32 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.298 Inches Minimum And 0.453 Inches Maximum |
| Fastener Length: | 1.969 Inches Minimum And 2.031 Inches Maximum |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Height: | 0.089 Inches Minimum And 0.099 Inches Maximum |
| Extended Washer Diameter: | 0.427 Inches Minimum And 0.447 Inches Maximum |
| Extended Washer Thickness: | 0.025 Inches Minimum And 0.030 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 4037 |
| Screw Material Document And Classification: | Ams 6300 Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium Or Zinc |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Fed Spec 1st Treatment Response Or Qq-z-325 Fed Spec 2nd Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-10R32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.