

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN52541618 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-274-0585 |
| Schedule B: | 7415.33.8050 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN525-416-18 Specifications

| | |
|-----------------------------------|-------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 1.125 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.437 Inches Nominal |
| Head Height: | 0.101 Inches Nominal |
| Extended Washer Diameter: | 0.500 Inches Nominal |
| Extended Washer Thickness: | 0.028 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 2330 |
| Screw Surface Treatment: | Cadmium Or Zinc |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-416-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.