

P/N AN525-416-8

Description

Fastener Length: 1/2", Thread: 1/4-28, Thread Length: 3/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN5254168

Minimum Qty (MOQ): 25

NSN: 5305-00-167-3631

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N AN525-416-8 Specifications

| Thread Class: | За |
|------------------------------------------------------|--------------------------------------------------------------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Minimum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.427 Inches Minimum And 0.447 Inches Maximum |
| Head Height: | 0.096 Inches Minimum And 0.106 Inches Maximum |
| Extended Washer Diameter: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Extended Washer Thickness: | 0.028 Inches Minimum And 0.033 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 8630 Or Steel Comp 4037 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Fed Spec 1st Treatment Response Or Qq-z-325 Fed Spec 2nd Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN525-416-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN525-416-8 and selecting the quantity you