

## P/N AN525-416R16

## **Description**

length: 1", grip: 19/32", thread: 1/4-28, cadmium plated steel, philips recess, AN525 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: AN525416R16

Minimum Qty (MOQ): 20

NSN: 5305-00-637-6395

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N AN525-416R16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.335 Inches Minimum
Fastener Length:	0.969 Inches Minimum And 1.031 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.437 Inches Nominal
Head Height:	0.101 Inches Nominal
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.028 Inches Minimum And 0.033 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 2330
Screw Surface Treatment:	Cadmium And Zinc
Screw Surface Treatment Document And Classification:	An-p-61 /canceled/ Fed Spec 1st Treatment Response Or An-p-32 /canceled/ Fed Spec 2nd Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN525-416R16">https://military-fasteners.com/screws/machine+screws/AN525-416R16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN525-416R16">https://military-fasteners.com/screws/machine+screws/AN525-416R16</a> and selecting the quantity you