

Description

Fastener Length: 25/32", Thread: 8-36, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN525812
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-167-3659
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN525-8-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.719 Inches Minimum And 0.789 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	100000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-689,cond C4 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium Or Zinc
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.