

Description

Fastener Length: 25/32", Thread: 8-36, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN525812 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-167-3659 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN525-8-12 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 0.719 Inches Minimum And 0.789 Inches Maximum |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.312 Inches Nominal |
| Head Height: | 0.082 Inches Minimum And 0.092 Inches Maximum |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.023 Inches Minimum And 0.028 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 36 |
| Minimum Tensile Strength: | 100000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-689,cond C4 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium Or Zinc |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.