

Description

Fastener Length: 19/32", Thread: 8-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN52583210
Minimum Qty (MOQ):	5
NSN:	5305-00-637-8279
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN525-832-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.656 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300,g40370 Assn Std 1st Material Response Or Mil-s-6050,g86300 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate Or Chromate Zinc
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec 1st Treatment Response Or Astm B633,type 2,fe/zn 13 Assn Std 2nd Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	88044-an525 Government Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.