



★ FASTENERS

Military-Fasteners.com

P/N AN525-832-7

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 3/8", AN525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN5258327 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-180-1474 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N AN525-832-7 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Minimum |
| Fastener Length: | 0.438 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.312 Inches Nominal |
| Head Height: | 0.082 Inches Minimum And 0.092 Inches Maximum |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.023 Inches Minimum And 0.028 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-689,c4-canceled Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate Zinc |
| Screw Surface Treatment Document And Classification: | An-p-61 Mil Std 1st Treatment Response And Mil-p-6889,type 1-canceled Mil Spec 2nd Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.