

Description

Fastener Length: 7/16", Thread: 8-32, Thread Length: 3/8", AN525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5258327
Minimum Qty (MOQ):	10
NSN:	5305-00-180-1474
Schedule B:	7318.15.6080
ECCN:	9A991



P/N AN525-832-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum
Fastener Length:	0.438 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-689,c4-canceled Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate Zinc
Screw Surface Treatment Document And Classification:	An-p-61 Mil Std 1st Treatment Response And Mil-p-6889,type 1-canceled Mil Spec 2nd Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.