

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5258328
Minimum Qty (MOQ):	100
NSN:	5305-00-507-9281
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN525-832-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum
Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.087 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 2330
Screw Material Document And Classification:	Qq-s-689 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium Or Zinc
Thread Series Designator:	Unc
Departure From Cited Designator:	As Mod By Surface Treatment

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.