

# P/N AN525-832-8

## **Description**

Fastener Length: 1/2", Thread: 8-32, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: AN5258328

Minimum Qty (MOQ): 100

NSN: 5305-00-507-9281

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N AN525-832-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum
Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.087 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 2330
Screw Material Document And Classification:	Qq-s-689 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium Or Zinc
Thread Series Designator:	Unc
Departure From Cited Designator:	As Mod By Surface Treatment

# **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN525-832-8">https://military-fasteners.com/screws/machine+screws/AN525-832-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN525-832-8">https://military-fasteners.com/screws/machine+screws/AN525-832-8</a> and selecting the quantity you