

P/N AN525-832R11

Description

length: 11/16", grip: 9/32", thread: 8-32, cadmium plated steel, philips recess, AN525 series screw

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN525832R11

Minimum Qty (MOQ): 100

NSN: 5305-00-281-8876

Schedule B: 7318.15.6080


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN525-832R11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.406 Inches Nominal
Head Style:	Fillister Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-689,cond C4 /canceled/ Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Zinc And Chromate
Screw Surface Treatment Document And Classification:	An-p-61 /canceled/ Assn Std 1st Treatment Response And Tt-p-1757,ty 1 Fed Spec 2nd Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN525-832R11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN525-832R11 and selecting the quantity you