

**Description**

length: 11/16", grip: 9/32", thread: 8-32, cadmium plated steel, philips recess, AN525 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN525832R11
Minimum Qty (MOQ):	100
NSN:	5305-00-281-8876
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN525-832R11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.406 Inches Minimum
<b>Fastener Length:</b>	0.406 Inches Nominal
<b>Head Style:</b>	Fillister Extended Washer
<b>Head Diameter:</b>	0.312 Inches Nominal
<b>Head Height:</b>	0.082 Inches Minimum And 0.092 Inches Maximum
<b>Extended Washer Diameter:</b>	0.375 Inches Nominal
<b>Extended Washer Thickness:</b>	0.023 Inches Minimum And 0.028 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel
<b>Screw Material Document And Classification:</b>	Qq-s-689,cond C4 /canceled/ Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Zinc And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	An-p-61 /canceled/ Assn Std 1st Treatment Response And Tt-p-1757,ty 1 Fed Spec 2nd Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832R11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.