

# P/N AN525-832R11

Military-Fasteners.com

#### Description

length: 11/16", grip: 9/32", thread: 8-32, cadmium plated steel, philips recess, AN525 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AN525832R11
Minimum Qty (MOQ):	100
NSN:	5305-00-281-8876
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN525-832R11 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.406 Inches Nominal
Head Style:	Fillister Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-689,cond C4 /canceled/ Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Zinc And Chromate
Screw Surface Treatment Document And Classification:	An-p-61 /canceled/ Assn Std 1st Treatment Response And Tt-p-1757,ty 1 Fed Spec 2nd Treatment Response
Thread Series Designator:	Unc

### **How to Order**

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/AN525-832R11</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.