

Description

length: 1-1/8", grip: 23/32", thread: 8-32, cadmium plated steel, philips recess, AN525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN525832R18
Minimum Qty (MOQ):	100
NSN:	5305-00-281-8874
Schedule B:	7318.15.6080
ECCN:	9A991.D
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN525-832R18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.298 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	1.094 Inches Minimum And 1.156 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 8630 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium Or Zinc
Screw Surface Treatment Document And Classification:	Qq-p-416 Fed Spec 1st Treatment Response Or Qq-z-325 Fed Spec 2nd Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832R18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.