

Description

length: 1-3/8", grip: 31/32", thread: 8-32, cadmium plated steel philips recess, AN525 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN525832R22 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-273-5349 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN525-832R22 Specifications

| | |
|-----------------------------------|-----------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 1.375 Inches Nominal |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.312 Inches Nominal |
| Head Height: | 0.087 Inches Nominal |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.023 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel Comp 2330 |
| Screw Surface Treatment: | Cadmium Or Zinc |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-832R22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.