

P/N AN525-832R28

Description

length: 1-3/4", grip: 1-11/32", thread: 8-32, cadmium plated steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN525832R28

Minimum Qty (MOQ): 50

NSN: 5305-00-630-9203

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN525-832R28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum And 0.437 Inches Maximum
Fastener Length:	1.719 Inches Minimum And 1.781 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium Or Cadmium And Chromate Or Cadmium And Phosphate Or Zinc Or Zinc And Chromate Or Zinc And Phosphate
Screw Surface Treatment Document And Classification:	Q-p-416 Fed Spec 13th Treatment Response Or Qq-p-416 Fed Spec 2nd Treatment Response Or Qq-b-416 Fed Spec 3rd Treatment Response Or Qq-z-325 Fed Spec 4th Treatment Response Or Qq-z-325 Fed Spec 6th Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN525-832R28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN525-832R28 and selecting the quantity you