

P/N AN525-832R32

Description

length: 2", grip: 1-19/32", thread: 8-32, cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS35206-253

SKU / Model: AN525832R32

Minimum Qty (MOQ): 10

NSN: 5305-00-984-6201

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN525-832R32 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Minimum
Fastener Length:	2.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN525-832R32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.