

**Description**

length: 1/2", grip: 1/8", thread: 8-36, cadmium plated steel, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN5258R8
Minimum Qty (MOQ):	100
NSN:	5305-00-180-0004
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN525-8R8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.272 Inches Minimum And 0.422 Inches Maximum
<b>Fastener Length:</b>	0.469 Inches Minimum And 0.531 Inches Maximum
<b>Head Style:</b>	Round Extended Washer
<b>Head Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.082 Inches Minimum And 0.092 Inches Maximum
<b>Extended Washer Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Extended Washer Thickness:</b>	0.023 Inches Minimum And 0.028 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 8630 Or Steel Comp 4037
<b>Screw Material Document And Classification:</b>	Mil-s-6050 Mil Spec 1st Material Response Or Ams 6300 Assn Std 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium Or Zinc
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec 1st Treatment Response Or Qq-z-325 Fed Spec 2nd Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525-8R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.