

**Description**

length: 11/16", grip: 9/32", thread: 10-32, aluminum - philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN525D10R11
Minimum Qty (MOQ):	25
NSN:	5305-00-576-7809
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



## P/N AN525D10R11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.297 Inches Minimum And 0.453 Inches Maximum
<b>Fastener Length:</b>	0.656 Inches Minimum And 0.719 Inches Maximum
<b>Head Style:</b>	Round Extended Washer
<b>Head Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Height:</b>	0.089 Inches Minimum And 0.099 Inches Maximum
<b>Extended Washer Diameter:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Extended Washer Thickness:</b>	0.025 Inches Minimum And 0.030 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Screw Material:</b>	Aluminum Alloy 2024
<b>Screw Material Document And Classification:</b>	Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Screw Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D10R11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.