

Description

length: 1/2", grip: 1/8", thread: 10-32, aluminum, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN525D10R8
Minimum Qty (MOQ):	50
NSN:	5305-00-702-7270
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



P/N AN525D10R8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum
Fastener Length:	0.500 Inches Nominal
Head Style:	Roof
Head Diameter:	0.437 Inches Nominal
Head Height:	0.094 Inches Nominal
Locking Feature:	Pellet
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Aluminum Alloy
Screw Material Document And Classification:	Qq-a-225/6 Fed Spec Single Material Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D10R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.