



Military-Fasteners.com

P/N AN525D416R10

Description

Fastener Length: 21/32", Thread: 1/4-28, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | AN525D416R10 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-057-2504 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991. |
| National Motor Freight: | 013680, Alum Screws |



* See page 2 for technical characteristics

P/N AN525D416R10 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.289 Inches Minimum And 0.453 Inches Maximum |
| Fastener Length: | 0.594 Inches Minimum And 0.656 Inches Maximum |
| Head Style: | Round Extended Washer |
| Head Diameter: | 0.427 Inches Minimum And 0.447 Inches Maximum |
| Head Height: | 0.096 Inches Minimum And 0.106 Inches Maximum |
| Extended Washer Diameter: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Extended Washer Thickness: | 0.028 Inches Minimum And 0.033 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Screw Material: | Aluminum Alloy 2024 |
| Screw Material Document And Classification: | Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response |
| Screw Surface Treatment: | Anodize |
| Screw Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D416R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.