



Military-Fasteners.com

P/N AN525D832-8

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN525D8328
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-207-3929
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N AN525D832-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.266 Inches Minimum And 0.422 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.099 Inches Maximum
Extended Washer Diameter:	0.427 Inches Minimum And 0.447 Inches Maximum
Extended Washer Thickness:	0.025 Inches Minimum And 0.030 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D832-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.