

**Description**

Fastener Length: 13/32", Thread: 8-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN525D832R6
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-584-8279
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws

NO IMAGE  
AVAILABLE

## P/N AN525D832R6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.235 Inches Minimum And 0.390 Inches Maximum
<b>Fastener Length:</b>	0.344 Inches Minimum And 0.406 Inches Maximum
<b>Head Style:</b>	Round Extended Washer
<b>Head Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.082 Inches Minimum And 0.092 Inches Maximum
<b>Extended Washer Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Extended Washer Thickness:</b>	0.023 Inches Minimum And 0.028 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Screw Material:</b>	Aluminum Alloy 2024
<b>Screw Material Document And Classification:</b>	Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Anodize
<b>Screw Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D832R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.