

Description

Fastener Length: 13/32", Thread: 8-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN525D832R6
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-584-8279
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



* See page 2 for technical characteristics

P/N AN525D832R6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.235 Inches Minimum And 0.390 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Screw Material:	Aluminum Alloy 2024
Screw Material Document And Classification:	Qq-a-200/3 Fed Spec Single Material Response Or Qq-a-225/6 Fed Spec Single Material Response
Screw Surface Treatment:	Anodize
Screw Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN525D832R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.