

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN52610327
Minimum Qty (MOQ):	40 EA
NSN:	5305-00-151-2781
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN526-1032-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Button
Head Diameter:	0.425 Inches Minimum And 0.448 Inches Maximum
Head Height:	0.118 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-671 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN526-1032-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.