

P/N AN526-1032R28

Description

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN5261032R28

Minimum Qty (MOQ): 100 EA

NSN: 5305-00-150-9402

Schedule B: 7318.15.4000

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN526-1032R28 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 1.750 Inches Minimum |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.425 Inches Minimum And 0.448 Inches Maximum |
| Head Height: | 0.118 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-671 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 3 Type And 7c Style |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN526-1032R28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.